

# T-AirWeld 820

614220

The T-AirLine Series headtops offer lightweight and comfortable protection in many industrial applications. The T-AirLine range is manufactured in accordance with the latest respiratory regulations. It provides protection for eye and face and is ideal in environments where the highest possible levels of protection are required.

**CE EN 14594: 2005 Class 3A / 3B**

## Main Applications

- Welding / Grinding

## Main Features

- Respiratory protection
- Eye and protection
- ADF lens for welding / grinding
- Adjustable head harness
- Strong and flexible PE breathing hose.
- Equipped comfortable face seal.
- Unique low airflow indicator.
- Comfortable easy to adjust airflow

## Spare parts

- 660213 Headgear with Airflow indicator
- 661368 T-AirLine regulator with belt
- 660048 Charcoal filter
- 661370 Hose with Bayonet connectors
- 661470 Sweatband



**614  
220**

Reference	614220
EN Standard	EN14594:2005
Class	3A / 3B
NPF	200
Working pressure	3 – 7 bar (Max 10)
Airflow	170 – 350 Adjustable
Weight of regulator incl. hose (g)	330
Noise level	< 59dB
Temperature range (°C)	-10 - + 50
Type of lens	ADF
Optical class	1/2/1/1
Viewing area	95 x 85 mm
Size ADF	133 x 114 x 9 mm
Lens shade	9-13 Variable
Lens state	Shade 3.5
Shade control	Internal
Sensors	4
On/off	Fully automatic
Power supply	Solar cells, lithium battery
Switch time	1/25,000 s.from Light to Dark
Sensitivity	adjust by infinitely dial knob
Delay time dark to light	0.1~1.0s by infinitely dial knob
Grind modus	Yes
Low TIG amps	≥2amps/DC; ≥4amps/AC
Approval lens	EN175B DINplus, CE,CSA,ANSI Z87.1, AS/NZS Approval
Weight of headtop (g)	640
Quantity per box	1